



USER GUIDE MILITARE AUTOMATIC

# MILITARE AUTOMATIC REF. AM1020



- A - Water-resistant crown with locking protective lever
- B - Small second
- C - Date display
- D - Hour hand treated with luminous coating
- E - Minute hand treated with luminous coating



Position 0: The watch is working and water resistance is guaranteed. The crown is locked thanks to the patented protective lever.

Position 1: Set the date

## SETTING THE TIME

1. Unlock the protective lever: rotate the protective lever up, and then lower the vanishing crown device. Get over the resistance of the click due to the lock catch.


**WARNING:** In this position water resistance is not guaranteed and the crown is not protected. It is still possible to set the time, date and wind the movement.

Repeatedly opening and closing the lever can affect the mechanism, do so only when necessary to set the time


2. Setting the time: once the lever is unlocked, pull out the crown completely to the second click. Rotate the crown clockwise to set the time. In this position water resistance is not guaranteed. After setting the time, return the crown firmly to its initial position and lock the protective lever. To fully lock, the protective lever must be placed in the low position (Pos.1).

In this position the watch is water-resistant to its rated depth.

### Patented Crown Vanishing Locking Device



Pos.1 Locked Position



Pos.2 Unlocked Position

**WARNING:** The lever is designed to block the crown when the watch is worn. If the strap is not fastened around the wrist, security of the crown is not ensured.

## **WINDING THE WATCH**

1. Unlock the protective lever as explained in the «setting the time» section.
2. Pull the crown to the first click and turn crown clockwise 15-20 rotations to fully wind the movement.
3. When the watch has been rewound, the power reserve indicator hand will raise and reach the non-red area.

Note: When the watch has not been worn or wound for more than 35 hours, it is recommended that it should be rewound with a few clockwise turns on the crown, to ensure sufficient power reserve and accurate operation. In this position water resistance is not guaranteed.

## **SPECIFICATIONS**

### **Movement:**

Anonimo CAL. 110013, Automatic Sellita caliber SW260-1 11 1/2, 47 jewels, 28'800 A/h, stop-seconds, power reserve 42 hours.

### **Water Resistance:**

12 ATM